

# Product datasheet

Specifications



## APC Netshelter Rack Automatic Transfer Switch, 1U, 10A, 230V, C14 IN, 12 C13 OUT, 50/60Hz

AP4421A

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage 230 V AC 1 phase

Product Or Component Type Automatic transfer switch

Main Output Voltage 230 V AC 1 phase

Input Connection Type IEC 60320 C14 10 A 2P + E

Number Of Rack Unit 1U

Provided Equipment  
Mounting hardware  
Rack mounting brackets  
Serial configuration cable

### Physical

Colour Black

Height 4.4 cm

Width 43.2 cm

Depth 23.6 cm

Net Weight 3.93 kg

Mounting Location Front

Mounting Preference No preference

Mounting Mode Rack-mounted

Mounting Position Horizontal

### Input

Network Frequency 50/60 Hz

[In] Rated Current 10 A

Permissible Voltage 207...253 V

Max Line Current 10 A

Load Capacity 2000 VA

### Output

Number Of Power Socket Outlets 12 IEC 60320 C13 10 A 2P + E

Number Of Power Socket Outlets 12

---

Protection Type	Without circuit breaker
-----------------	-------------------------

## Conformance

---

Product Certifications	EN 55022 class A FCC part 15 class A
------------------------	---

---

Standards	EN 55022 class A FCC part 15 class A
-----------	---

## Environmental

---

Ambient Air Temperature For Operation	-5...45 °C
---------------------------------------	------------

---

Relative Humidity	5...95 %
-------------------	----------

---

Operating Altitude	0...10000 ft
--------------------	--------------

---

Ambient Air Temperature For Storage	-25...65 °C
-------------------------------------	-------------

---

Storage Relative Humidity	5...95 %
---------------------------	----------

---

Storage Altitude	0...15240 m
------------------	-------------

## Packing Units

---

Unit Type Of Package 1	PCE
------------------------	-----

---

Number Of Units In Package 1	1
------------------------------	---

---

Package 1 Height	11.000 cm
------------------	-----------

---

Package 1 Width	35.000 cm
-----------------	-----------

---

Package 1 Length	60.000 cm
------------------	-----------

---

Package 1 Weight	5.420 kg
------------------	----------

---

Unit Type Of Package 2	P12
------------------------	-----

---

Number Of Units In Package 2	40
------------------------------	----

---

Package 2 Height	126.000 cm
------------------	------------

---

Package 2 Width	80.000 cm
-----------------	-----------

---

Package 2 Length	120.000 cm
------------------	------------

---

Package 2 Weight	230.000 kg
------------------	------------

## Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Take-back Transparency RoHS/REACH

## Resource performance

Take-Back Program Available

---

## Well-being performance

Lead Free

---

Mercury Free

---

Rohs Exemption Information Yes

---

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Compliant  
[EU RoHS Declaration](#)

---

**China Rohs Regulation** [China RoHS declaration](#)

---

**Environmental Disclosure** [Product Environmental Profile](#)

---

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

**Circularity Profile** [End of Life Information](#)

---