

Product datasheet

Specifications



APC Netshelter Rack Automatic Transfer Switch, 1U, 20A, 200/208V, 2 L6-20 IN, 8 C13, 1 C19 OUT, 50/60Hz

AP4430A

Overview

Lead Time Usually in Stock

Main

Main Input Voltage 200 V AC 1 phase
208 V

Product Or Component Type Automatic transfer switch

Main Output Voltage 200 V AC 1 phase
208 V

Input Connection Type NEMA L6-20P 16 A 2P + E

Number Of Rack Unit 1U

Cable Length 2.44 m

Number Of Cables 2

Provided Equipment Mounting hardware
Rack mounting brackets
Serial configuration cable

Physical

Colour Black

Height 4.4 cm

Width 43.2 cm

Depth 23.6 cm

Net Weight 4.83 kg

Mounting Location Front
Rear

Mounting Preference No preference

Mounting Mode Rack-mounted

Mounting Position Horizontal

Input

Network Frequency 50/60 Hz

[In] Rated Current 20 A

Permissible Voltage 180...220 V

Max Line Current 20 A

Input Current Limits 20 A

Load Capacity	3300 VA
---------------	---------

Output

Max Current Draw	20 A
------------------	------

Number Of Power Socket Outlets	8 IEC 60320 C13 12 A 2P + E 1 IEC 60320 C19 16 A 2P + E
--------------------------------	------------------------------------------------------------

Number Of Power Socket Outlets	9
--------------------------------	---

Protection Type	Without circuit breaker
-----------------	-------------------------

Power Cable Length	2.44 m
--------------------	--------

Conformance

Standards	EN 55022 class A FCC part 15 class A
-----------	-----------------------------------------

Environmental

Ambient Air Temperature For Operation	-5...45 °C
---------------------------------------	------------

Relative Humidity	5...95 %
-------------------	----------

Operating Altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature For Storage	-25...65 °C
-------------------------------------	-------------

Storage Relative Humidity	5...95 %
---------------------------	----------

Storage Altitude	0...15240 m
------------------	-------------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	23.6 cm
------------------	---------

Package 1 Width	60 cm
-----------------	-------

Package 1 Length	35.6 cm
------------------	---------

Package 1 Weight	6.6 kg
------------------	--------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)





Take-back Transparency RoHS/REACH


Resource performance

 Take-Back Program Available

Well-being performance

 Lead Free

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive [Compliant](#)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee [The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins](#)

Circularity Profile [End of Life Information](#)