Evidence Eraser Series: SATA/IDE Hard Disk Eraser-CS01

Using data overwrite in erase mode had been proven safe and effective method to prevent the risk of data retrieval by others. The HDD is cleaned and can safety be discarded or recycled.

TP series eraser allows all business to seek an economic way to perform the safest hard drive cleaning and recycling work. There are 9 types of erase mode that can provide various application levels, from general, corporate, banking and military use.

	▲ ONOFF	A POWER	▲ 🛫	
HDD/SSD ER	ASER		UP	ок
			Ĩ	Õ
			DOWN	
	V SATA V POW	NGRat BR	▼ DE	

Function & Features

- 9 Erase modes: ①Quick Erase, ②Full Erase, ③DoD Erase(DoD5220.22-M), ④3-Pass Erase(CSEC ITSG-06, ⑤HMG Enhanced IS 5), ⑥7-Pass Erase(VSITR), ⑦Custom Erase, ⑧ Secure Erase, ⑨Enhanced Secure Erase
- Export all log reports via PC or HDD, including HDD serial number, processing tasks, time and results.
- Invisible Confirm Mark- After checking HDD info, it can display whether the HDD has been processed erase tasks or not.
- Support SATA/IDE HDD and SSD.
- Support HPA/DCO.

Specification Table

Name	TP Evidence Eraser		
Model	CS01		
Port	Single port erasing		
Maximum speed	7.2 GB/min (120MB/sec)*(Actual performance would depend on HDD quality)		
Erase Function	Quick Erase, Full Erase, DoD Erase(DoD5220.22-M), 3-Pass Erase(CSEC ITSG-06, HMG Enhanced IS 5), 7-Pass Erase(VSITR), Custom Erase, Secure Erase, Enhanced Secure Erase		
Connector	SATA-HDD, IDE-HDD, HDD power port		
Interface	1.8"/2.5"/3.5" SATA 1.0/2.0/3.0 HDD, SSD, IDE HDD		
Display	2x20 backlight Monochrome LCD display		
LED status	LED light: Red(Fail)/Green(Pass)/Yellow(Powering) on each slot		
Control key	4 types of keys: ▲/UP, ▼/DOWN, ◯/OK, X/ESC		
Operating type	Stand-alone operation, Output log via PC and HDD		
Eraser Language	English		
Power Supply	HDD auto power control		
	Adjustable voltage 100V-240V, 50/60Hz		
	12V 5A		
Temperature	Working: 5℃ ~45℃ ; Storage-20℃ ~85℃		
Humidity	Working: 20%~80%; Storage: 5%~95%		
Certification	CE, FCC, RoHS		
Size	15(L) x 8(W) x 3(H) cm		
Weight	450 g		